



FLAT HIGH-QUALITY GLYCEROPHTALIC PAINT

BATILAC MAT

INDEX N°A 25

Definition

Glycerophtalic jelly paint, silky flat finish.

Purpose

BATILAC MAT is intended for the renovation of ceilings, doors, walls, etc. that are already painted. Also recommended for new surfaces requiring the use of a very effective paint for a perfect finish such as plaster, plasterboard, primed woodwork or ingrain paper.

Description

Very good masking power, making it possible to obtain a perfect finish with only one coat, particularly in the case of renovation work. Easy to apply, doesn't run or streak and doesn't have to be touched up.

Application

Brush, roller or spray.

Colour range

With concentrated universal tinting colours.

Recommendations

BATILAC MAT should be applied to clean, dry, sound, adherent and dust-free surfaces. Prime new woodwork or very absorbent plaster with BATILIN or IMPRIMAT.

Old peeling or chalky paint should be washed off or stripped.

Treat ferrous metals with BATIFER or ANTICO PH, depending on their condition.

Composition : Main binder: altered alkyd resins. Pigment: titanium oxide. Charges: lithopone. Solvent: white spirit.

Identification : AFNOR Classification: Family I, class 4a. Fineness of grind: 8 (Hegman scale). Density at 20°C: 1.8 ± 0.1 . Dry extract: $85\% \pm 2\%$. Viscosity at 20°C: 60 poises.

Features : Yield: 8 to 9 m² per kg (depending on surface porosity). Dust dry drying: 2 hours.

Dry: 5 hours - Recoating: 12 hours.

Dilution : Absorbent surfaces: 3 to 5% white spirit - Non-absorbent surfaces: 0 to 2% white spirit.

Equipment cleaning : With white spirit, immediately after use.

Packaging : 1kg, 5kg, 15kg and 25kg net.

Storage : One year in the original hermetically-sealed packaging.

CHABAUD S.A.S.

380, rue Terre de Roy - ZI - 34748 VENDARGUES Cedex (FRANCE) - Tél. (33) 04 67 87 20 20 - Fax (33) 04 67 87 19 93

internet : chabaud.com / e-mail : chabaud@chabaud.com