



# SATIN-FINISH GLYCEROPHTALIC LACQUER

## BATILAC SATIN

INDEX N°A 30

### Definition

Glycerophtalic paint, with a satin, non-yellowing finish, for interiors and exteriors.

### Purpose

BATILAC SATIN can be used for all satin finishing work and particularly woodwork, doors, ferrous metals, bathrooms, kitchens, etc.

### Description

Excellent quality/price ratio; easy to apply; doesn't run or spatter; good coverage and high-build; its satin surface is long-lasting, washable, tough and easy to maintain.

### Application

Brush, roller or spray.

### Colour range

With concentrated universal tinting colours.

### Recommendations

Apply BATILAC SATIN to clean, dry, sound and totally adherent surfaces. Prime new woodwork or plaster with BATILIN or IMPRIMAT.

Before using, apply a coat of RENOVFER or ANTICO PH to ferrous metals, depending on their condition.

**Composition :** Main binder: alkyd resins and glycerophtalic resins- Pigment: rutile titanium oxide - Solvent: white spirit.

**Identification :** AFNOR Classification: Family I, class 4a - Fineness: 9 (Hegman scale) - Density:  $1.74 \pm 0.1$ . Dry extract:  $85\% \pm 2\%$ . Viscosity at 20°C: 38 poises.

**Features :** Yield: 9 to 10 m<sup>2</sup> per kg (depending on surface porosity). Drying - dust dry: 2 hours - Dry: 4 hours - Recoating: 12 hours.

**Dilution :** BATILAC SATIN is ready for use.

As a first coat or to spray on, add 6 to 7% white spirit.

**Equipment cleaning :** With white spirit, immediately after use.

**Packaging :** 1kg, 5kg, 15kg, and 25kg net.

CHABAUD S.A.S.

380, rue Terre de Roy - ZI - 34748 VENDARGUES Cedex (FRANCE) - Tél. (33) 04 67 87 20 20 - Fax (33) 04 67 87 19 93

internet : [chabaud.com](http://chabaud.com) / e-mail : [chabaud@chabaud.com](mailto:chabaud@chabaud.com)